
## **Historic, Archive Document**

Do not assume content reflects current scientific knowledge, policies, or practices.



En 83 Et

ET-47



May 1935

## A HUMIDIFIER USED IN SMALL INCUBATORS

By L. G. Jones, Division of Cereal and Forage Insect Investigations, Bureau of Entomology and Plant Quarantine, U. S. Department of Agriculture

The humidifier herein described has given satisfactory service in small incubators where certain constant-temperature and relative humidity tests have been made with eggs, larvae, and adults of various insects incidental to research on the European corn borer.

The humidifying chamber proper consists of a nonrusting metal box, 6 by 6 by 18 inches (fig. 2, A), with a removable top (B). An air inlet (C) is provided in the upper half of one end of the box and an air outlet (D) about 1 inch in diameter in the upper half of the opposite end. The air channel in the box is chevroned with side baffles constructed of strips of ordinary blotting paper (E) sewed with fine copper wire to stiff nonrusting wire frames (F). The baffling is held upright by small brass bolts attached to the sides of the box. A supply of water (distilled to prevent deposits accumulating on the baffles) is maintained in the box at a level just below the end openings. The absorption rate of the blotting paper is sufficiently rapid to keep a constant supply of moisture available on the baffles.

The air circulator is an electric "whisk broom" (G) with the broom portion and part of the handle or blower sawed off, controlled by a hygrostat. That portion of the blower retained is inserted through the air inlet (C) of the box.

In operation the pump draws air from the incubator, forces it through the air channel, where it absorbs moisture from the baffles, and returns it to the incubator.

A humidifier of this type has been found to maintain relative humidities up to 96 percent, with differentials not exceeding 2 percent, within comparatively small chambers (15 to 30 cubic feet) when controlled by a hair hygrostat, as described by Baker and Arbuthnot (Baker, W. A., and Arbuthnot, K. D. An Incubator Room. Jour. Econ. Ent. 24: 444-449, illus. 1931).

Explanation of Illustrations

Figure 1 .- Humidifier as in operation.

Figure 2.—Humidifier with top removed, showing parts.

Boal yall

WHOMESTER WITH HE WAS IN SECURIOR W

Tovostigation Surequest Sand Formed Inner

them all address the control of the property of the control of the

The head of the company of the consists of a consisting metal box, 6 by 8 by 18 inches (fig. 2 A), with a resovable top (8). An air inlet (0) is provided in the upper half of one and of the cox and an air outlet (0) should 1 inches a dissert in the upper half of the opposite and The sir charge in the last of the constructed of atripe of ordinary blotting paper are constructed of atripe of ordinary blotting paper with the copper wire to attif constructing also imposed with the copper wire to attif constructing also inches of the box of an apply of water (distilled to crevist deposits accommutating on the buffles) as an anticiped in the box at a level just below the and openings. The absorption according on the buffles of the buffles acqualume available on the buffles.

The air circulator is an electric "enish brone" (0) with the brone particular and part of the handle or blower sense of the controlled by a notice of the player retained is inscribed through the wir lefet (2) of the box.

In operation the pump draws not from the incubators lesses it cannot be seen to the invitation, and recurre the invitation.

A humidiffer of this type has bein found to onicialn relative humidities of to 96 percent, with differentials not examined 2 corcent, within correctively small chambers (15 to 30 cmits from) when controlled by a hair scatter, an described by Rayer and Aran bust (2 lest, W. A., and broadled) and broadled (2 lest, W. A., and broadled).

Explanation of Illustration

noticised at as reliablement. I oruge

Figure 2. -- Humidifiur with top recoved. shoulds partie.




Figure 1. - Humidifier as in operation.






Figure 2. - Humidifier with top removed, showing parts.



Pipers 1. - Smithfree as in operations



referred to - Description with the property of the later of